

Nowata Printing Company

Electronic Pre-press Specifications

We accept CDs, DVDs, and utilize a T1 line for internet access and FTP transfer

Customer supplied file requirements for offset printing:

1. Laser prints should accompany any customer provided file. One composite laser print per page. Include any special instructions on the print.
2. Files should be clearly identified. Designate any spot color you wish to use.
3. All supporting files including graphics, pictures, scans, artwork and ads should be included with the layout file.
4. When scanning images, a resolution of twice the line screen should be used.
(i.e. Newsprint stock requires 100 lines per inch; resolution should be 200 dots per inch)
5. All digital files should be in CMYK color mode. Do not send files in RGB, LAB, or Index color mode. All files should be binary EPS or TIFF format. Do not send JPEG, GIF, PSD, Picture Viewer, or EPS files with JPEG compression.
6. Include all font files (screen and printer) used in publication, including fonts used in EPS files. Do not include fonts that are not used in the document.
7. Check finished size and image size for accuracy. All bleeds should extend .25" outside edge of page. (Finished size is the physical page size in your document and the physical size of the final printed piece.)

Software:

Adobe Pagemaker
Adobe Photoshop
Adobe Illustrator
Adobe InDesign
Adobe Acrobat
QuarkXpress
WAR ftp

Hardware:

PowerMac
PC (Windows 98)
Apple XServe
Stingray 25" Imagesetter
HP 1050C color proofer
Scitex 12' x 18" flatbed scanner
Nikon CoolPix 5000 digital camera

FTP Address:

216.61.239.53

Call to request user name and password